

Automatic Pineapple Peeler KA-730M Spec Sheet

|                       |                       |  |  |
|-----------------------|-----------------------|--|--|
| Model                 |                       | KA-730M  |  |
| Size                  |                       | 210mm(W) × 385mm(D) × 500mm(H) *Main unit only   |  |
| Weight                |                       | 13kg(Main unit)、15kg(Including option parts)   |  |
| Power Supply          |                       | AC100-240V 50/60Hz (3P grounding-type plug)  |  |
| Power Consumption     |                       | 250W (max) / 5W (standby mode)   |  |
| Performance           | Use for               | One fruit chosen from Mango, Melon, or Grapefruit  |  |
|                       | Fruit size            | Mango: height 100-160mm<br>Melon: height 130-220mm (diameter: -180mm)<br>Grapefruit: height 100-180mm (diameter: -200mm) |  |
|                       | Process time          | Mango: 7.5 / minute, not including loading time  |  |
|                       | Continuous operation  | Unlimited<br>(10 minutes interval recommended every 2 hours)   |  |
|                       | Inspection            | Required (by metal detection)  |  |
| Environment           | Temperature, humidity | 0-40°C under 85RH%   |  |
|                       | Water/dust proof      | IP54 equivalent (except for the back and bottom)   |  |
|                       | Cleaning              | Body   | Flow water, shower (high pressure cleaning not possible) |
|                       |                       | Arm  | Washable (dishwasher, alcohol, hypo-water available)     |
| Prongs                |                       | Washable (dishwasher, alcohol, hypo-water available)   |  |
| Material              |                       | SUS303/304/304WPB/420J2(Blade)/430/440/ POM  |  |
| Maintenance           |                       | Wash it at least once per day when in use.<br>Check that all parts are functioning correctly.                            |  |
| Warranty              |                       | One year from purchase or<br>within 1,000 hours of total usage time  |  |
| Inspection conditions |                       | After completion of installation and operation, check  |  |