

Automatic Pineapple Peeler FAP-3000 Spec Sheet

Model		FAP-3000	
Size		1250mm(W) × 550mm(D) × 1500mm(H)	
Weight		110kg	
Power Supply		AC100-240V 50/60Hz (3P grounding-type plug)	
Power Consumption		720W (max) / 12W (standby mode)	
Supply Air		Max. 0.8 MPa (Recommended: 0.5-0.8 MPa), Supply port: $\phi$ 8	
Performance	Use for	Pineapple	
	Fruit size	Pineapple: height 100-170mm (diameter: 60-160mm)	
	Process time	8 sec/ piece	
	Continuous operation	8 hours	
	Inspection	Required (by metal detection)	
Environment	Temperature, humidity	0-40°C under 85RH%	
	Water/dust proof	IP55 equivalent	
	Cleaning	Body	Flow water, shower (high-pressure cleaning not possible)
		Arm	Washable (dishwasher, alcohol, hypo-water available)
Prongs		Washable (dishwasher, alcohol, hypo-water available)	
Material		SUS303/304/304WPB/420J2(Blade)/430/440/ POM/Aluminum	
Maintenance		Wash it at least once per day when in use. Check that all parts are functioning correctly.	
Warranty		One year from purchase or within 1,000 hours of total usage time	
Inspection conditions		After completion of installation and operation, check	