

Automatic Mango Peeler KA-730 Spec Sheet

Model		KA-730	
Size		210mm(W) × 380mm(D) × 450mm(H) * Excluding protrusions and accessories	
Weight		13kg(* Including accessories)	
Power supply		AC100~130、200~240V 50/60Hz (3P grounding type plug) * Overseas specifications available	
Power consumption		150W(max) / 4W(standby mode)	
Performance	Use for	Mango (Melon with option parts sold separately)	
	Fruit size	Mango: height 100~160mm Honeydew Melon: height 130~180mm(diameter: ~180mm)	
	Process time	7.5 / minute, excluding loading time	
	Continuous operation	Unlimited (10 minutes interval recommended every 2 hours)	
	Inspection	Required (by metal detection)	
Environment	Temperature, humidity	0~40°C 0~85RH% (Relative humidity)	
	Water/ dust proof	IP54 equivalent (except for the back and bottom)	
	Cleaning	Body	Flow water, shower (high pressure cleaning not possible)
		Arm	Washable (dishwasher, alcohol, hypo-water available)
Prongs		Washable (dishwasher, alcohol, hypo-water available)	
Material		SUS303/304/304WPB/430/440/D-SR1K6(blades)/POM	
Maintenance		Wash it at least once per day when in use. Check that all parts are functioning properly.	
Warranty		One year from purchase or within 500 hours of total usage time	
Inspection conditions		After completion of installation and operation check	