

Automatic Pineapple Peeler KA-750PM Spec Sheet

| | | | |
|-----------------------|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|
| Model | | KA-750PM | |
| Size | | 210mm(W) × 385mm(D) × 500mm(H) *Main unit only | |
| Weight | | 13kg(Main unit)、15kg(Including option parts) | |
| Power Supply | | AC100-240V 50/60Hz (3P grounding-type plug) | |
| Power Consumption | | 250W (max) / 5W (standby mode) | |
| Performance | Use for | Pineapple, Melon, Mango, Pumpkin (Kent) | |
| | Fruit size | Pineapple: height100-170mm (diameter: 60-160mm) Melon: height 130-220mm (diameter: -180mm) Mango: height100-160mm Pumpkin (Kent) : height 80-150mm(diameter: -200mm) | |
| | Process time | Pineapple: 7.5 / minute, not including loading time | |
| | Continuous operation | Unlimited (10 minutes interval recommended every 2 hours) | |
| | Inspection | Required (by metal detection) | |
| Environment | Temperature, humidity | 0-40°C under 85RH% | |
| | Water/dust proof | IP54 equivalent (except for the back and bottom) | |
| | Cleaning | Body | Flow water, shower (high pressure cleaning not possible) |
| | | Arm | Washable (dishwasher, alcohol, hypo-water available) |
| Prongs | | Washable (dishwasher, alcohol, hypo-water available) | |
| Material | | SUS303/304/304WPB/420J2(Blade)/430/440/ POM | |
| Maintenance | | Wash it at least once per day when in use. Check that all parts are functioning correctly. | |
| Warranty | | One year from purchase or within 1,000 hours of total usage time | |
| Inspection conditions | | After completion of installation and operation, check | |