

Automatic Pineapple Peeler KA-750 Spec Sheet

Model		KA-750	
Size		260mm(W) × 500mm(D) × 480mm(H) *Main unit only	
Weight		25kg(Main unit)、30kg(Including option parts)	
Power Supply		AC100~130、200~240V 50/60Hz (3P grounding type plug)	
Power Consumption		250W (max) / 5W (standby mode)	
Performance	Use for	Pineapple, Melon, Mango, Pumpkin (Kent)	
	Fruit size	Pineapple : height 100~170mm(diameter : 60~160mm) (Option parts for small pineapples sold separately) Honeydew Melon : height 130~180mm(diameter : ~180mm) Mango : height 100~160mm Pumpkin (Kent) : height 80~150mm(diameter : ~200mm)	
	Process time	Pineapple: 7.5 / minute, including loading time	
	Continuous operation	Unlimited (10 minutes interval recommended every 2 hours)	
	Inspection	Required (by metal detection)	
Environment	Temperature, humidity	0~40°C under 85RH%	
	Water/dust proof	IP54 equivalent (except for the back and bottom)	
	Cleaning	Body	Flow water, shower (high pressure cleaning not possible)
		Arm	Washable (dishwasher, alcohol, hypo-water available)
Prongs		Washable (dishwasher, alcohol, hypo-water available)	
Material		SUS303/304/304WPB/430/440/D-SR1K6 (Blades)/POM	
Maintenance		Wash it at least once per day when in use. Check that all parts are functioning properly.	
Warranty		One year from purchase or within 1,000 hours of total usage time	
Inspection conditions		After completion of installation and operation check	